elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



EC71025CR

JOINT PIPE-PIPE IP67 Ø25 mm - RED RAL3000 - EASYSYSTEM

Enclosures > Special application systems > Emergency line > Conduits and fittings > Joint conduit - conduit

Technical Symbols/Marks/Approvals

IP67 | UL94 V0 | GWT 960° | IK07 | CE | RoHS II | MADE IN ITALY

Norms

EN 61386-1 EN 61386-21

Description

Conduit-to-conduit coupling for connecting two pipes of the same diameter, made of impact-resistant rigid PVC-based technopolymer. Soft internal sealing ring for conduit tolerance compensation. IP67 protection degree. Self-extinguishing grade V0 according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1, EN 61386-21 standards.
Diameter 25 mm - Length 65 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC000939 - Coupler for installation tubes

Material	Plastic	**Material quality**	Polyvinyl chloride (PVC)	**Halogen free**	No
Surface protection	Untreated	**Colour**	Red	**Model**	Plug-in
UV resistant	Yes	**Quality of surface coating**	Uncoated	**Surface polished**	No
Surface brushed	No	**Suitable for nominal tube diameter**	25 mm	**Two-part**	No
With inspection opening and cover	No	**With lock function**	No	**Material sealing**	Rubber
With outer thread	No	**With inner thread**	No	**Separable**	No
Eccentric	No				

Technical Characteristics

length	65 mm

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8056351664035

Pack

25 NR

0.78 [kg]

8056351663793

Cardboard

250 NR

0.295x0.39x0.3 [m]

7.8 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.