elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



IMMAGINE RAPPRESENTATIVA — REPRESENTATIVE IMAGE

EC73020CR

BEND 90° IP67 Ø20 mm - RED RAL3000 - EASYSYSTEM

Enclosures > Special application systems > Emergency line > Conduits and fittings > Coupler bend conduit - conduit

Technical Symbols/Marks/Approvals

IP67 | UL94 V0 | GWT 960° | IK07 | CE | RoHS II | MADE IN ITALY

Norms

EN 61386-1 EN 61386-21

Description

90° conduit-to-conduit bend for connecting two pipes of the same diameter, made of impact-resistant rigid PVC-based technopolymer. Soft internal sealing ring for conduit tolerance compensation. IP67 protection degree. Self-extinguishing grade V0 according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1, EN 61386-21 standards.
Diameter 20 mm - bending radius 70 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC000936 - Bend for installation tubes

Material	Plastic	**Material quality**	Polyvinyl chloride (PVC)	**Halogen free**	No
Surface protection	Untreated	**Colour**	Other	**Model**	Plug-in
Diameter	20 mm	**Flexible**	No	**UV resistant**	Yes
Quality of surface coating	Uncoated	**Surface polished**	No	**Surface brushed**	No
Compressive strength class according to EN 61386-1	None	**Impact strength class according to EN 61386-1**	Medium (class 3 / 2 Joule)	**Suitable for nominal tube diameter**	20 mm
With sleeve	Yes	**Two-part**	No	**With inspection opening and cover**	No
Radius	70 mm	**Bend angle**	90 °		

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8056351663991

Pack

25 NR

0.85 [kg]

8056351663755

Cardboard

200 NR

0.295x0.39x0.3 [m]

6.8 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.