elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



EC74020

JOINT PIPE-PIPE IP67 Ø20 mm - GREY - SECURITY

Conduits and fittings > Accessories and fittings > Joints and fittings > Security system - ip67 fittings > Joint conduit - conduit

Technical Symbols/Marks/Approvals

IP67 | HF | GWT 850° | IK07 | CE | RoHS II | MADE IN ITALY

Norms

EN 61386-1 EN 61386-21

Description

Conduit-to-conduit coupling for connecting two pipes of the same diameter, made of co-molded impact-resistant and low-smoke emission technopolymers. IP67 protection degree. Self-extinguishing grade V2 according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 850 °C. Manufactured in compliance with EN 61386-1, EN 61386-21 standards.
Diameter 20 mm - Length 82 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC000939 - Coupler for installation tubes

Material	Plastic	**Material quality**	Polyethylene (PE)	**Halogen free**	Yes
Surface protection	Untreated	**Colour**	Grey	**Model**	Plug-in
UV resistant	Yes	**Quality of surface coating**	Uncoated	**Surface polished**	No
Surface brushed	No	**Suitable for nominal tube diameter**	20 mm	**Two-part**	No
With inspection opening and cover	No	**With lock function**	No	**Material sealing**	Rubber
With outer thread	No	**With inner thread**	No	**Separable**	No
Eccentric	No				

Technical Characteristics

length	82 mm

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download



Certification

Raccordi Security System_2023.pdf

Barcode

8050880883813

Pack

10 NR

0.115 [kg]

8057711591503

Cardboard

200 NR

0.295x0.39x0.21 [m]

2.3 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.