ECelettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



EC74116

JOINT PIPE-BOX IP67 Ø16 mm - GREY - SECURITY

Conduits and fittings > Accessories and fittings > Joints and fittings > Security system - ip67 fittings > Coupler conduit - box

Technical Symbols/Marks/Approvals

IP67 | HF | GWT 850° | IK07 | CE | RoHS II | MADE IN ITALY

Norms

EN 61386-1 EN 61386-21

Description

Conduit-to-box connector made of co-molded impact-resistant and low-smoke emission technopolymers. IP67 protection degree. Self-extinguishing grade V2 according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 850 °C. 1.5 mm metric pitch thread. Supplied with gasket and fixing locknut mounted. Manufactured in compliance with EN 61386-1, EN 61386-21 standards. Diameter 16 mm - Length 54 mm - Thread length 13 mm

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002326 - Cable plug for cable-/installation tube entry

Suitable for cable diameter	16 ÷ 16 mm	**Suitable for built-in installation box**	No	**Suitable for junction box**	Yes
Suitable for cable box	Yes	**Suitable for expansion ring**	No	**For tube diameter**	16 mm
Number of conduit lead-ins	1				

Technical Characteristics

length	54 mm	**thread length**	13 mm

Documentation available for download



Certification

Raccordi Security System_2023.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8050880883868

Pack

10 NR

0.109 [kg]

8057711591558

Cardboard

350 NR

0.295x0.39x0.21 [m]

3.815 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.