elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



EC75240

JOINT PIPE-SPIRAL CONDUIT IP65 Ø40-32 mm - GREY - SPEED SYSTEM

Conduits and fittings > Accessories and fittings > Joints and fittings > Speed system - ip65 fittings > Coupler conduit - spiral conduit > Conduit joints (spiral-rigid) - different diameters

Technical Symbols/Marks/Approvals

IP65 | UL94 V0 | GWT 960° | IK07 | CE | RoHS II | MADE IN ITALY

Norms

EN 61386-1 EN 61386-21

Description

Connector for the connection between a pipe and a spiral conduit of different diameters, made of shockproof technopolymer based on rigid PVC. Soft internal sealing ring for pipe tolerance compensation. IP65 protection rating. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.
Pipe diameter 40 mm - Conduit diameter 32 mm

Etim

GROUP EG000003 - Protective hose systems

CLASS EC001172 - Coupler for corrugated plastic hoses

Degree of protection (IP)	IP65	**Material**	Plastic	**Material quality**	Other
Colour	Grey	**Model**	Straight	**Working temperature**	-5 ÷ 60 °C
Nominal size	32 ÷ 40 mm				

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8050507872145

Pack

5 NR

0.2225 [kg]

8050507872152

Cardboard

100 NR

0.39x0.295x0.3 [m]

4.45 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.