

## EC75525

### FLEXIBLE BEND PIPE-BOX IP65 Ø25 mm - GREY - SPEED SYSTEM



Conduits and fittings > Accessories and fittings > Joints and fittings > Speed system - ip65 fittings > Coupler bend conduit - conduit > Flexible bend (conduits-box)

#### Technical Symbols/Marks/Approvals

|      |            |             |      |    |         |                     |
|------|------------|-------------|------|----|---------|---------------------|
| IP65 | UL94<br>V0 | GWT<br>960° | IK07 | CE | RoHS II | MADE<br>IN<br>ITALY |
|------|------------|-------------|------|----|---------|---------------------|

#### Norms

EN 61386-1 EN 61386-21

## Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC000936 - Bend for installation tubes

|                                                           |           |                                                      |                            |                                          |         |
|-----------------------------------------------------------|-----------|------------------------------------------------------|----------------------------|------------------------------------------|---------|
| <b>Material</b>                                           | Plastic   | <b>Material quality</b>                              | Polyvinyl chloride (PVC)   | <b>Halogen free</b>                      | No      |
| <b>Surface protection</b>                                 | Untreated | <b>Colour</b>                                        | Grey                       | <b>Model</b>                             | Plug-in |
| <b>Diameter</b>                                           | 25 mm     | <b>Flexible</b>                                      | Yes                        | <b>UV resistant</b>                      | Yes     |
| <b>Quality of surface coating</b>                         | Uncoated  | <b>Surface polished</b>                              | No                         | <b>Surface brushed</b>                   | No      |
| <b>Compressive strength class according to EN 61386-1</b> | None      | <b>Impact strength class according to EN 61386-1</b> | Medium (class 3 / 2 Joule) | <b>For nominal tube diameter</b>         | 25 mm   |
| <b>With sleeve</b>                                        | Yes       | <b>Two-part</b>                                      | No                         | <b>With inspection opening and cover</b> | No      |
| <b>Radius</b>                                             | 250 mm    | <b>Bend angle</b>                                    | 90 °                       |                                          |         |

## Technical Characteristics

length 230 mm

## Barcode



8050507872459

**Pack**

35 NR

2.1245 [kg]



8050507872466

**Cardboard**

140 NR

0.605x0.4x0.26 [m]

8.498 [kg]