elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

**TECHNICAL DATA SHEET**




# EC8102036

## CABLE TIE PA 6.6 - 200x3,6 mm - BLACK

Conduits and fittings > Accessories and fittings > Fixings > Cable ties > Cable tie > Black

### Technical Symbols/Marks/Approvals

UL94 V2 | UV | CE | RoHS II | MADE IN PRC

### Norms

EN 62275

## Description

Cable tie made of impact-resistant polyamide-based technopolymer, Halogen Free according to EN 60754-1, EN 60754-2, and EN 60754-3 standards. Self-extinguishing grade V2 according to UL94 standard. High UV resistance. High resistance to oils and mineral fats. Manufactured in compliance with EN 62275 and UL standards where applicable.

## Etim

### GROUP EG000049 - Fasteners

### CLASS EC000046 - Cable tie

| | | | | | |
|---|---|---|---|---|---|
| **Material** | Plastic | **Material quality** | Polyamide (PA) | **Halogen free** | Yes |
| **Surface protection** | Untreated | **Colour** | Black | **Transparent** | No |
| **Type of fastening** | None | **Model** | Internal toothing | **Band width** | 3.6 mm |
| **Length belt/tape/tie** | 200 mm | **Bundle diameter** | 0 ÷ 53 mm | **Min. tensile strength** | 18.2 kg |
| **Operating temperature** | -40 ÷ 85 °C | **Mounting temperature** | -5 ÷ 60 °C | **Band closure** | Plastic lip/-cam |
| **UV-stable according to ASTM D6779** | No | **Fluorescent** | No | **Detectable** | No |
| **Text strip** | None | **Releasable closure** | No | **VG approval** | No |
| **MIL approval** | No | **UL approval** | No | **Inflammability class of insulation material according to UL94** | V2 |



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

## Barcode



8050880884285

**Pack**

100 NR

0.11 [kg]



8057711591978

**Cardboard**

5000 NR

5.5 [kg]



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.