



**EC8103648**

**CABLE TIE PA 6.6 - 360x4,8 mm - BLACK**

Conduits and fittings > Accessories and fittings > Fixings > Cable ties > Cable tie > Black



**Technical Symbols/Marks/Approvals**



**Norms**

EN 62275

**Etim**

**GROUP EG000049 - Fasteners**

**CLASS EC000046 - Cable tie**

|                                          |           |                             |                   |                                                                      |                  |
|------------------------------------------|-----------|-----------------------------|-------------------|----------------------------------------------------------------------|------------------|
| <b>Material</b>                          | Plastic   | <b>Material quality</b>     | Polyamide (PA)    | <b>Halogen free</b>                                                  | Yes              |
| <b>Surface protection</b>                | Untreated | <b>Colour</b>               | Black             | <b>Transparent</b>                                                   | No               |
| <b>Type of fastening</b>                 | None      | <b>Model</b>                | Internal toothing | <b>Band width</b>                                                    | 4.8 mm           |
| <b>Length belt/tape/tie</b>              | 360 mm    | <b>Bundle diameter</b>      | 0-102 mm          | <b>Min. tensile strength</b>                                         | 22.2 kg          |
| <b>Operating temperature</b>             | -40-85 °C | <b>Mounting temperature</b> | -5-60 °C          | <b>Band closure</b>                                                  | Plastic lip/-cam |
| <b>UV-stable according to ASTM D6779</b> | No        | <b>Fluorescent</b>          | No                | <b>Detectable</b>                                                    | No               |
| <b>Text strip</b>                        | None      | <b>Releasable closure</b>   | No                | <b>VG approval</b>                                                   | No               |
| <b>MIL approval</b>                      | No        | <b>UL approval</b>          | No                | <b>Inflammability class of insulation material according to UL94</b> | V2               |

## Barcode



8050880884346

**Pack**

100 NR

0.24 [kg]



8057711592036

**Cardboard**

3000 NR

0.305x0.565x0.145 [m]

7.2 [kg]