elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



EC8104390

CABLE TIE PA 6.6 - 430x9,0 mm - BLACK

Conduits and fittings > Accessories and fittings > Fixings > Cable ties > Cable tie > Black

Technical Symbols/Marks/Approvals

UL94 V2 | UV | CE | RoHS II | MADE IN PRC

Norms

EN 62275

Description

Cable tie made of impact-resistant polyamide-based technopolymer, Halogen Free according to EN 60754-1, EN 60754-2, and EN 60754-3 standards. Self-extinguishing grade V2 according to UL94 standard. High UV resistance. High resistance to oils and mineral fats. Manufactured in compliance with EN 62275 and UL standards where applicable.

Etim

GROUP EG000049 - Fasteners

CLASS EC000046 - Cable tie

Material	Plastic	**Material quality**	Polyamide (PA)	**Halogen free**	Yes
Surface protection	Untreated	**Colour**	Black	**Transparent**	No
Type of fastening	None	**Model**	Internal toothing	**Band width**	9 mm
Length belt/tape/tie	430 mm	**Bundle diameter**	0 ÷ 110 mm	**Min. tensile strength**	79.4 kg
Operating temperature	-40 ÷ 85 °C	**Mounting temperature**	-5 ÷ 60 °C	**Band closure**	Plastic lip/-cam
UV-stable according to ASTM D6779	No	**Fluorescent**	No	**Detectable**	No
Text strip	None	**Releasable closure**	No	**VG approval**	No
MIL approval	No	**UL approval**	No	**Inflammability class of insulation material according to UL94**	V2

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8050880884377

Pack

100 NR

0.85 [kg]



8057711592067

Cardboard

1000 NR

0.305x0.58x0.14 [m]

8.5 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.