elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET

ECAE20080B

EXTERNAL ANGLE DIM. 200X80 WHITE

Canalizaciones > Pared y techo > Canales portacables > Serie cp - accesorios > Ángulo exterior para canal de pared

Technical Symbols/Marks/Approvals

IP40 | IK07 | GWT 650° | CE | RoHS II | MADE IN ITALY

Estándares

EN 50085-1 EN50085-2-1

Descripción

Ángulo externo para cambio de dirección a 90°. Enganche a presión en la canaleta

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC000872 - Outer corner for wall duct

Degree of protection (IP)	IP40	**Material**	Plastic	**Material quality**	Acrylonitrile butadiene styrene (ABS)
Halogen free	Sí	**Anti-bacterial treatment**	No	**Surface protection**	Untreated
Colour	White	**Impact strength**	IK07	**Width**	200 mm
Depth	80 mm	**Model**	Moulded hood	**RAL-number**	9001
Mounting method cover	Spanned	**With protective foil**	No	**Working temperature**	-5-60 °C
With cable fixing clip	No	**With duct connector**	Sí	**Bottom perforation**	No
Angle	90-90 °	**Number of covers**	1	**Cover width 1**	200 mm
Symmetric	Sí				

Documentation available for download

Certification

Canali CPH IMQ_CA02.06517_2020.pdf

Certification

Canali e Minic Serie MC-CP.pdf

Certification

LICENCE 669941_CP-MC.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8050880885664

Cardboard

4 NR

0.39x0.295x0.15 [m]

1.3 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.