

ECCP60100B

CABLE TRUNKING WITH COVER DIM. 60X100 WHITE



Canalizaciones > Pared y techo > Canaletas portacables >
Serie cp - canales > Canal de pared portamecanismos >
Blanco



IMMAGINE
RAPPRESENTATIVA

EC

REPRESENTATIVE
IMAGE

Technical Symbols/Marks/Approvals



Estándares

EN 50085-1 EN 50085-2-1

Description

Cable duct made of self-extinguishing rigid PVC technopolymer. The bottom is pre-drilled for fixing with screws and anchors. A front-hinged lid is included.


Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC001938 - Wall duct

Degree of protection (IP)	IP40	Material	Plastic	Material quality	Polyvinyl chloride (PVC)
Halogen free	No	Anti-bacterial treatment	No	Colour	White
Impact strength	IK07	Width	60 mm	Depth	100 mm
Length	2 m	Usable cross section	5332 mm ²	RAL-number	9001
Mounting method cover	Spanned	With protective foil	No	Working temperature	-5-60 °C
Number of plug-in partitions	0	With cable fixing clip	No	With duct connector	No
Bottom perforation	No	Number of covers	1	Cover width 1	60 mm
Symmetric	Sí	Covers included	Sí	Construction type rectangular	Sí
Construction rear wall (inner side)	Perforated				

Documentation available for download



Instruction booklet

Istruzioni canali.pdf



Certification

Canali e Minic Serie
MC-CP.pdf



Certification

LICENCE
669941_CP-MC.pdf

Barcode



8050880887484

Cardboard

24 MT

0.26x0.26x2.03 [m]

25.5 [kg]



8055035961897

Pallet

288 MT

1.2x0.8x2.2 [m]

306 [kg]