

ECCP6060B

CABLE TRUNKING WITH COVER DIM. 60X60 WHITE

Canalizaciones > Pared y techo > Canaletas portacables >
Serie cp - canales > Canal de pared portamecanismos >
Blanco



Technical Symbols/Marks/Approvals



Estándares

EN 50085-1 EN 50085-2-1

Description

Cable duct made of self-extinguishing rigid PVC technopolymer. The bottom is pre-drilled for fixing with screws and anchors. A front-hinged lid is included.


Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC001938 - Wall duct

Degree of protection (IP)	IP40	Material	Plastic	Material quality	Polyvinyl chloride (PVC)
Halogen free	No	Anti-bacterial treatment	No	Surface protection	Untreated
Colour	White	Impact strength	IK07	Width	60 mm
Depth	60 mm	Length	2 m	Usable cross section	3046 mm²
RAL-number	9001	Mounting method cover	Spanned	With protective foil	No
Working temperature	-5-60 °C	Number of plug-in partitions	0	With cable fixing clip	No
With duct connector	No	Bottom perforation	No	Number of covers	1
Cover width 1	60 mm	Symmetric	Sí	Covers included	Sí
Construction type rectangular	Sí	Construction rear wall (inner side)	Perforated		

Documentation available for download



Instruction booklet

Istruzioni canali.pdf



Certification

Canali e Minic Serie
MC-CP.pdf



Certification

LICENCE
669941_CP-MC.pdf

Barcode



8050880887521

Cardboard

32 MT

0.26x0.18x2.027 [m]

20.4992 [kg]



8055035961958

Pallet

576 MT

1.2x0.8x2.2 [m]

368.9856 [kg]