

ECCPH8080



HALOGEN FREE CABLE TRUNKING WITH COVER DIM. 80X80 GREY

Canalizaciones > Pared y techo > Canaletas portacables > Cph
- canales libres de halógenos > Cph - canales libres de
halógenos



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Technical Symbols/Marks/Approvals

HF	IK07	IP40	UL94 V2	GWT 960°	-25°	+90°	CE
RoHS II	MADE IN ITALY						

Estándares

EN 50267-2-1 EN 50267-2-2 IEC 60754-1 IEC 60754-2 EN 50085-1

EN 50085-2-1

Description

Cable duct made of halogen-free technopolymer. Self-extinguishing according to UL94 - V2 standards at 1.6 mm. Resistance to abnormal heat: up to 960°C (GWT). Dimensional stability between -25°C and +90°C. Bottom pre-drilled for fixing with screws and anchors. Front-locking cover included.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC001938 - Wall duct

Degree of protection (IP)	IP40	Material	Plastic	Material quality	Polycarbonate (PC)/ABS
Halogen free	Yes	Anti-bacterial treatment	No	Surface protection	Untreated
Colour	Grey	Impact strength	IK07	Width	80 etim.un.eu570448.abb
Depth	80 etim.un.eu570448.abb	Length	2 m	Usable cross section	5620 etim.un.eu570126.abb
RAL-number	7035	Mounting method cover	Spanned	With protective foil	No
Working temperature	-25-90 etim.un.eu570073.abb	Number of plug-in partitions	2	With cable fixing clip	No
With duct connector	No	Bottom perforation	No	Number of covers	1
Cover width 1	80 etim.un.eu570448.abb	Symmetric	Yes	Covers included	Yes
Construction type rectangular	Yes	Construction rear wall (inner side)	Perforated		

Documentation available for download



Instruction booklet
Istruzioni canali.pdf



Certification
Canali CPH
IMQ_CA02.06517_2020.pdf

Barcode



8050880887835
Cardboard
30 MT
0.26x0.18x2.027 [m]
26.001 [kg]



8055035962306
Pallet
360 MT
1.2x0.8x2.2 [m]
312.012 [kg]