

ECGFE28N

FLEXIBLE SPIRAL CONDUIT 23114 Ø28 mm - 30 m - BLACK



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Tuberías y accesorios > Electroflex > Tubo electroflex flexibles
> Gfe - 23114 > Gfe - 23114 > Negro

Technical Symbols/Marks/Approvals

UL94
V0

GWT
960°

CE

RoHS II

UL

MADE
IN
ITALY

Estándares

EN 61386-1 EN 61386-23 UL 1696

Etim

GROUP EG000003 - Protective hose systems

CLASS EC001177 - Protective plastic hose

Material	Polyvinyl chloride (PVC)	Halogen free	No	Colour	Black
UV resistant	Yes	Working temperature	5-60 etim.un.eu570073.abb	Nominal diameter	28 etim.un.eu570448.abb
Inner diameter	28 etim.un.eu570448.abb	Outer diameter	33.5 etim.un.eu570448.abb	Compressive strength	320 etim.un.eu570020.abb
Bending radius, static	280 etim.un.eu570448.abb	Tensile strength	100 etim.un.eu570020.abb	Approved according to DIN EN 61386-23	Yes
Approved according to UR	Yes	Approved according to CSA	No	Material filament	Helix of rigid plastic
Plain interior	Yes	Plain exterior	No	Flexibility	Flexible
Approved according to N	No				

Documentation available for download

CERTIFICATE OF COMPLIANCE

Certification

Certificato UL
GUAINE E173313-
2021.pdf

Barcode



8050880888559

Cardboard

30 MT

0.55x0.55x0.19 [m]

6.201 [kg]



8057711593873

Pallet

1950 MT

403.065 [kg]