

ECGFE40N

FLEXIBLE SPIRAL CONDUIT 23114 Ø40 mm - 30 m - BLACK



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Tuberías y accesorios > Electroflex > Tubo electroflex flexibles
> Gfe - 23114 > Tubo de protección flexible plástico > Negro

Technical Symbols/Marks/Approvals



Estándares

EN 61386-1 EN 61386-23 UL 1696


Etim

GROUP EG000003 - Protective hose systems

CLASS EC001177 - Protective plastic hose

Material	Polyvinyl chloride (PVC)	Halogen free	No	Colour	Black
UV resistant	Sí	Working temperature	5-60 °C	Nominal diameter	40 mm
Inner diameter	40 mm	Outer diameter	46.4 mm	Compressive strength	320 N
Bending radius, static	400 mm	Tensile strength	100 N	Approved according to DIN EN 61386-23	Sí
Approved according to UR	Sí	Approved according to CSA	No	Material filament	Helix of rigid plastic
Plain interior	Sí	Plain exterior	No	Flexibility	Flexible
Approved according to N	No				

Documentation available for download



Barcode



8050880888597

Cardboard

30 MT

0.67x0.67x0.19 [m]

9 [kg]



8057711593910

Pallet

1440 MT

432 [kg]