

ECGFE50N

FLEXIBLE SPIRAL CONDUIT 23114 Ø50 mm - 30 m - BLACK



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Tuberías y accesorios > Tubo guaina spiral > Tubo espiral (electroflex) > Serie gfe - 23114 - 320 n > Tubo espiralado flexible plástico > Negro

Technical Symbols/Marks/Approvals



Estándares

EN 61386-1 EN 61386-23 UL 1696

Etim

GROUP EG000003 - Protective hose systems

CLASS EC001177 - Protective plastic hose

Material	Polyvinyl chloride (PVC)	Halogen free	No	Colour	Black
UV resistant	Sí	Working temperature	5-60 °C	Nominal diameter	50 mm
Inner diameter	50 mm	Outer diameter	57.2 mm	Compressive strength	320 N
Bending radius, static	500 mm	Tensile strength	100 N	Approved according to DIN EN 61386-23	Sí
Approved according to UR	Sí	Approved according to CSA	No	Material filament	Helix of rigid plastic
Plain interior	Sí	Plain exterior	No	Flexibility	Flexible
Approved according to N	No				

Documentation available for download



Certification

Certificato UL
GUAINA E173313-
2021.pdf



Certification

Serie Guaine e
raccordi
IMQ_CA02.06109_
2023.pdf

Barcode



8050880888603

Cardboard

30 MT

0.75x0.75x0.23 [m]

12 [kg]



8057711593927

Pallet

660 MT

264 [kg]