

ECGFE60

FLEXIBLE SPIRAL CONDUIT 23114 Ø60 mm - 30 m - GREY



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Tuberías y accesorios > Electroflex > Tubo electroflex flexibles
> Gfe - 23114 > Tubo de protección flexible plástico > Gris

Technical Symbols/Marks/Approvals

UL94 V0	GWT 960°	CE	RoHS II	UL US	MADE IN ITALY
------------	-------------	----	---------	----------	---------------------

Estándares

EN 61386-1 EN 61386-23 UL 1696

Etim

GROUP EG000003 - Protective hose systems

CLASS EC001177 - Protective plastic hose

Material	Polyvinyl chloride (PVC)	Halogen free	No	Colour	Grey
UV resistant	Sí	Working temperature	5-60 °C	Nominal diameter	60 mm
Inner diameter	60 mm	Outer diameter	68 mm	Compressive strength	320 N
Bending radius, static	600 mm	Tensile strength	100 N	Approved according to DIN EN 61386-23	Sí
Approved according to UR	Sí	Approved according to CSA	No	Material filament	Helix of rigid plastic
Plain interior	Sí	Plain exterior	No	Flexibility	Flexible
Approved according to N	No				

Documentation available for download



Certification

Certificato UL
GUAINE E173313-
2021.pdf

Barcode



8050880888610

Cardboard

30 MT

0.96x0.96x0.26 [m]

15 [kg]



8057711593934

Pallet

300 MT

150 [kg]