

ECK11104N

MULTIPLE SOCKET 4 GANGS 10/16A BLACK



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Residencial > Series de utilidades > Artículos de uso
doméstico > Base de zÓcalo múltiple > Base de zÓcalo
múltiple > Base de zÓcalo múltiple de 45° con cable

Technical Symbols/Marks/Approvals

IP20

UL94
V0

GWT
750°

CE

RoHS II



MADE
IN
PRC

Estándares

CEI 23-50 CEI 23-124

Etim

GROUP EG000013 - Domestic switching devices

CLASS EC000330 - Socket outlet combination

Degree of protection (IP)	IP20	RAL-number (similar)	9005	Material	Plastic
Material quality	Thermoplastic	Halogen free	No	Anti-bacterial treatment	No
Surface protection	Untreated	Surface finishing	Glossy	Colour	Black
Transparent	No	Impact strength	IK09	Working temperature	-15-35 etim.un.eu570073.abb
Compatible with Apple HomeKit	No	Compatible with Google Assistant	No	Compatible with Amazon Alexa	No
IFTTT support available	No	Overvoltage protection	No	With miniature fuse	No
With on/off switch	Yes	Rotated central insert	Yes	Nominal current	16 etim.un.eu570459.abb
Core cross section	1 etim.un.eu570126.abb	Number of socket outlets with protective contact CEE 7/3 (type F)	4	Number of socket outlets British Standard BS 1363	0
Number of socket outlets Italian standard type Bipasso	4	Number of socket outlets Italian standard type P11	0	Number of socket outlets Italian standard type P17	0
Number of socket outlets Italian standard type P30	0	Number of universal multi standard sockets	0	Number of socket outlets Swiss standard type 13	0
Number of socket outlets Swiss standard type 15	0	Number of socket outlets Swiss standard type 23	0	Number of socket outlets Swiss standard type 25	0
Type of mains connection	Italian type P17	NEMA designation	None	Housing shape	Rectangular
Number of socket outlets CEE 7/1 (no protective contact)	0	Number of socket outlets CEE 7/16 (EURO)	0	Number of socket outlets with earth pin	4
Number of cold device socket outlets	0	Number of socket outlets Danish standard (earthing pin, type K)	0	Number of socket outlets with protective contact CEE 7/5 (type E)	0
Number of NEMA-outlets	0	Residual current circuit breaker (RCCB)	No	Mains filter	No
Number of other socket outlets	0	Number of USB connections	0	Overcurrent protection	No
Max. connected load	3500 etim.un.eu570054.abb	With cover	No	Length of power cord	1.5 m
Type of plug	Straight	Directly pluggable (without power cord)	No	Angle rotated central insert	45°

Barcode



8053676570232

Unit

1 NR

0.37 [kg]



8059307219594

Cardboard

40 NR

0.4x0.44x0.29 [m]

14.8 [kg]