



## ECK51006

### PORTABLE HALOGEN PROJECTOR IP54 500W WITH SUPPORT

Residencial > Series de utilidades > Iluminación > Proyectores  
> Luz de obra > Halógeno



#### Technical Symbols/Marks/Approvals



## Etim

GROUP EG000027 - Luminaires

CLASS EC000346 - Building site lighting luminaire

|                                                                                  |                   |                                 |             |                         |                 |
|----------------------------------------------------------------------------------|-------------------|---------------------------------|-------------|-------------------------|-----------------|
| Degree of protection (IP)                                                        | IP54              | Impact strength                 | IK09        | Width                   | 180 mm          |
| Height                                                                           | 145 mm            | Depth                           | 150 mm      | Nominal voltage         | 220-240 V       |
| Connection type                                                                  | Other             | With light source               | Sí          | Housing material        | Aluminium       |
| Protection class according to IEC 61140                                          | II                | Lamp holder                     | R7s         | Lamp type               | LV halogen lamp |
| Housing colour                                                                   | Black             | Colour of light                 | White       | With socket outlet      | No              |
| Energy efficiency class of the light source according to EU regulation 2019/2015 | C                 | With wheels                     | No          | With stand holder       | No              |
| With stand                                                                       | No                | Colour of stand                 | Yellow      | With protective cover   | Sí              |
| Material protective cover                                                        | Steel             | Rated lifetime L70/B50 at 25 °C | 2000 h      | Suitable for lamp power | 500-500 W       |
| Rated luminous flux according to IEC 62722-2-1                                   | 8700 lm           | Colour temperature              | 3000-3000 K | Type of wiring          | Ending          |
| Conductor cross section                                                          | 1 mm <sup>2</sup> | Connection cable length         | 1.3 m       |                         |                 |

## Barcode



8033954877086

Unit

1 NR

2.1667 [kg]



8059606150253

Cardboard

8 NR

17.3336 [kg]