

ECMA2010

MINITRUNKING HINGED LID AND SELF-ADHES. BOTTOM 20X10



Canalizaciones > Pared y techo > Mini-canales > Serie ma - cintas adhesivas de doble cara con tapa integrada > canal de pared para conducción de cableado > Blanco



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Technical Symbols/Marks/Approvals

IK04	IP40	UL94 V0	GWT 960°	CE	RoHS II	MADE IN ITALY
------	------	------------	-------------	----	---------	---------------------

Estándares

EN 50085-1 EN 50085-2-1

Description

Mini-trunking made of self-extinguishing rigid PVC technopolymer. With adhesive strip for permanent attachment. Integrated lid with snap closure.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC000059 - Mini/maxi trunking

Degree of protection (IP)	IP40	Material	Plastic	Material quality	Polyvinyl chloride (PVC)
Halogen free	No	Anti-bacterial treatment	No	Surface protection	Untreated
Colour	White	Transparent	No	Impact strength	IK04
Type of fastening	Self-adhesive	Width	20 mm	Height	10 mm
Length	2 m	Usable cross section	128 mm²	RAL-number	9001
With protective foil	No	Working temperature	-5-60 °C	Cover model	With film hinge
Suitable for circuit integrity	No	Number of permanent partitions	0	Number of plug-in partitions	0
With cable fixing clip	No	With duct connector	No	Delivery on roll	No
Pre-stamping	No				

Barcode



8054320282358

Cardboard

100 MT

0.195x0.102x2.025 [m]

9.5 [kg]