

## ECMA2075-SAC

### MINITRUNKING HINGED LID AND SELF-ADHES. BOTTOM 20X7.5 BAGS OF 10 BARS



IMMAGINE  
RAPPRESENTATIVA



REPRESENTATIVE  
IMAGE

Canalizaciones > Pared y techo > Mini-canales > Serie ma -  
cintas adhesivas de doble cara con tapa integrada > canal de  
pared para conducción de cableado > Blanco (paquete de 10)

#### Technical Symbols/Marks/Approvals

|      |      |            |             |    |         |                     |
|------|------|------------|-------------|----|---------|---------------------|
| IK04 | IP40 | UL94<br>V0 | GWT<br>960° | CE | RoHS II | MADE<br>IN<br>ITALY |
|------|------|------------|-------------|----|---------|---------------------|

#### Estándares

EN 50085-1 EN 50085-2-1

## Description

Mini-trunking made of self-extinguishing rigid PVC technopolymer. With adhesive strip for permanent attachment. Integrated lid with snap closure.

## Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC000059 - Mini/maxi trunking

|                                |               |                                |          |                              |                          |
|--------------------------------|---------------|--------------------------------|----------|------------------------------|--------------------------|
| Degree of protection (IP)      | IP40          | Material                       | Plastic  | Material quality             | Polyvinyl chloride (PVC) |
| Halogen free                   | No            | Anti-bacterial treatment       | No       | Surface protection           | Untreated                |
| Colour                         | White         | Transparent                    | No       | Impact strength              | IK04                     |
| Type of fastening              | Self-adhesive | Width                          | 20 mm    | Height                       | 7.5 mm                   |
| Length                         | 2 m           | Usable cross section           | 94 mm²   | RAL-number                   | 9001                     |
| With protective foil           | No            | Working temperature            | -5-60 °C | Cover model                  | With film hinge          |
| Suitable for circuit integrity | No            | Number of permanent partitions | 0        | Number of plug-in partitions | 0                        |
| With cable fixing clip         | No            | With duct connector            | No       | Delivery on roll             | No                       |
| Pre-stamping                   | No            |                                |          |                              |                          |

## Barcode



8056351667937

**Pack**

20 MT

1.534 [kg]



8056351668194

**Cardboard**

160 MT

12.272 [kg]