


ECMC2010B-SAC

MINITRUNKING FRONT-HOOKING LID 20X10 WHITE 1 COMPARTMENT BAGS OF 10 BARS



Canalizaciones > Pared y techo > Minicanales > Serie mc - con
tapa frontal > Minicanales > Blanco (paquete de 10)

Technical Symbols/Marks/Approvals



Estándares

EN 50085-1 EN 50085-2-1

Descripción

Mini-trunking made of self-extinguishing rigid PVC technopolymer. The bottom is pre-drilled for fastening with screws and anchors. The bottom is designed for quick fastening with silicone adhesives. The front-hinged lid is supplied assembled.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC000059 - Mini/maxi trunking

Degree of protection (IP)	IP40	Material	Plastic	Material quality	Polyvinyl chloride (PVC)
Halogen free	No	Anti-bacterial treatment	No	Surface protection	Untreated
Colour	White	Transparent	No	Impact strength	IK07
Type of fastening	Bottom perforation	Width	20 mm	Height	10 mm
Length	2 m	Usable cross section	126 mm²	RAL-number	9001
With protective foil	No	Working temperature	-5-60 °C	Cover model	Loose
Suitable for circuit integrity	No	Number of permanent partitions	0	Number of plug-in partitions	0
With cable fixing clip	No	With duct connector	No	Delivery on roll	No
Pre-stamping	No				

Documentation available for download



Instruction booklet

Istruzioni
minicanali.pdf



Certification

Canali e Minic Serie
MC-CP.pdf



Certification

LICENCE
669941_CP-MC.pdf

Barcode



8056351667708

Pack

20 MT

2 [kg]



8056351667968

Cardboard

100 MT

10 [kg]