

ECMC2020B

MINITRUNKING FRONT-HOOKING LID 20X20 WHITE 1 COMPARTMENT



Canalizaciones > Pared y techo > Mini-canales > Mc - con tapa frontal > Canal de pared para conducción de cableado > Blanco



Technical Symbols/Marks/Approvals

IK07	IP40	UL94 V0	GWT 960°	CE	RoHS II	Y	NF
MADE IN ITALY							

Estándares

EN 50085-1 EN 50085-2-1

Description

Mini-trunking made of self-extinguishing rigid PVC technopolymer. The bottom is pre-drilled for fastening with screws and anchors. The bottom is designed for quick fastening with silicone adhesives. The front-hinged lid is supplied assembled.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC000059 - Mini/maxi trunking

Degree of protection (IP)	IP40	Material	Plastic	Material quality	Polyvinyl chloride (PVC)
Halogen free	No	Anti-bacterial treatment	No	Surface protection	Untreated
Colour	White	Transparent	No	Impact strength	IK07
Type of fastening	Bottom perforation	Width	20 mm	Height	20 mm
Length	2 m	Usable cross section	264 mm²	RAL-number	9001
With protective foil	No	Working temperature	-5-60 °C	Cover model	Loose
Suitable for circuit integrity	No	Number of permanent partitions	0	Number of plug-in partitions	0
With cable fixing clip	No	With duct connector	No	Delivery on roll	No
Pre-stamping	No				

Documentation available for download



Instruction booklet

Istruzioni
minicanali.pdf

Barcode



8054320287629

Cardboard

90 MT

0.195x0.102x2.025 [m]

10.998 [kg]