


EC20116

6-MODULE TOWER ADAPTOR BOX 100 mm HOLE C.E DISTANCE-SLATE RAL 7021



Canalizaciones > Pared y techo > ZÓcalo y marco >
Accesorios de canalización > Adaptador de soluciones para canal de pared de conducción de cableado

Technical Symbols/Marks/Approvals

IP40	IK08	GWT 650°	CE	RoHS II		MADE IN ITALY
------	------	-------------	----	---------	--	---------------------

Estándares

EN 50085-1 EN 50085-2-1

Description

The 6/7-module 100 mm center-to-center appliance box can accommodate up to 7 Italian standard appliances or 3 multi-standard sockets. The large internal volume allows for the installation of any type of appliance. The box is composed of three assembled parts: the lower part, which snaps onto the trunking and the wall with 4 screws, and serves as an insulating base and a grid separating the various circuits. The upper part is specially shaped to accommodate the appliance mounting frames. The trunking cover, in addition to its protective function, gives the whole a harmonious and elegant shape.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling


CLASS EC000079 - Appliance box for skirting duct

Degree of protection (IP)	IP40	Mounting direction	Horizontal	Material	Plastic
Halogen free	Sí	Anti-bacterial treatment	No	Colour	Anthracite
Impact strength	IK08	RAL-number	7021	Working temperature	-5-60 °C
Decoration	None	Mounting method installation unit	Standard	Height baseboard duct	70 mm
Depth plinth skirting duct	20 mm	Number of device units	6	Equipped with	None

Technical Characteristics

Dimensiones 225 x 185 x 50 mm

Documentation available for download



Barcode



8033954876294

Unit

1 NR

0.3125 [kg]



8059307212687

Cardboard

8 NR

0.39x0.295x0.21 [m]

2.5 [kg]