


ECTG1220-2

RIGID CONDUIT 22211 Ø20 mm - 2 m

Tuberías y accesorios > Tubería > Tubos rígidos > Serie tg12 - pvc - 22211 > Tubo plástico para instalación eléctrica > Barra de 2 metros



Technical Symbols/Marks/Approvals



Estándares

EN 61386-1 EN 61386-21

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Sí	Material	Polyvinyl chloride (PVC)	Halogen free	No
Colour	Grey	RAL-number	7035	UV resistant	Sí
Suitable for underground installation	No	Operating temperature	-5-60 °C	Bending strength	Rigid
Compressive strength class according to EN 61386-1	Light (class 2 / 1 Joule)	Impact strength class according to EN 61386-1	Light (class 2 / 1 Joule)	With sleeve	No
Fire retardant version	Sí	Surface mounting	Sí	Suitable for installation on wood	Sí
Suitable for hollow wall installation	Sí	Suitable for concrete installation	No	Machine and systems installation	No
Suitable for underfloor installation (screed)	No	Suitable for outdoor installation	No	Inner diameter	17.9 mm
Outer diameter	20 mm	High conducting inner coating	No	With metre indication	No

Barcode




8054320285076

Cardboard

68 MT

6.868 [kg]



8057711598540

Pallet

1360 MT

2x0.61x0.63 [m]

137.36 [kg]