

ECTG1225

RIGID CONDUIT 22211 Ø25 mm - 3 m

Tuberías y accesorios > Tubería > Tubos rígidos > Tg12 - pvc - 22211 > Tg12 - pvc - 22211 > Barra de 3 metros



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Technical Symbols/Marks/Approvals



Estándares

EN 61386-1 EN 61386-21

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Yes	Material	Polyvinyl chloride (PVC)	Halogen free	No
Colour	Grey	RAL-number	7035	UV resistant	Yes
Suitable for underground installation	No	Operating temperature	-5-60 etim.un.eu570073.abb	Bending strength	Rigid
Compressive strength class according to EN 61386-1	Light (class 2 / 1 Joule)	Impact strength class according to EN 61386-1	Light (class 2 / 1 Joule)	With sleeve	No
Fire retardant version	Yes	Surface mounting	Yes	Suitable for installation on wood	Yes
Suitable for hollow wall installation	Yes	Suitable for concrete installation	No	Machine and systems installation	No
Suitable for underfloor installation (screed)	No	Suitable for outdoor installation	No	Inner diameter	22.5 etim.un.eu570448.abb
Outer diameter	25 etim.un.eu570448.abb	High conducting inner coating	No	With metre indication	No

Barcode




8054320285045

Cardboard

60 MT

8.184 [kg]



8057711598571

Pallet

1440 MT

3x0.61x0.63 [m]

196.416 [kg]