

ECTG1540

RIGID CONDUIT 33211 Ø40 mm - 3 m - BUNDLE 30



Tuberías y accesorios > Tubería > Tubos rígidos > Serie tg15 -
pvc - 33211 - 750 n > Tubo plástico para instalación eléctrica >
Barra de 3 metros



IMMAGINE
RAPPRESENTATIVA

EC REPRESENTATIVE
IMAGE

Technical Symbols/Marks/Approvals



Estándares

EN 61386-1 EN 61386-21


Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Sí	Material	Polyvinyl chloride (PVC)	Halogen free	No
Colour	Grey	RAL-number	7035	UV resistant	Sí
Suitable for underground installation	Sí	Operating temperature	-5-60 °C	Bending strength	Rigid
Compressive strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	Impact strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	With sleeve	No
Fire retardant version	Sí	Surface mounting	Sí	Suitable for installation on wood	Sí
Suitable for hollow wall installation	Sí	Suitable for concrete installation	No	Machine and systems installation	Sí
Suitable for underfloor installation (screed)	Sí	Suitable for outdoor installation	Sí	Inner diameter	35.9 mm
Outer diameter	40 mm	High conducting inner coating	No	With metre indication	No

Documentation available for download



Certification

Tubo Rigido TG15
e
Raccordi_2023.pdf



Certification

Tubo rigido
IMQ_EN835_2023-
01-12.pdf



Certification

LICENCE NF -
TG15 -2022 -
Licence - Certificat
Produits-14694838-
778138-
0000732340-
6.p....pdf

Barcode




8054320284727

Cardboard

30 MT

9.534 [kg]



8057711598892

Pallet

540 MT

3x0.61x0.63 [m]

171.612 [kg]