

ECTG1563

RIGID CONDUIT 33211 Ø63 mm - 3 m

Tuberías y accesorios > Tubería > Tubos rígidos > Tg15 - pvc - 33211 > Tubo plástico para instalación eléctrica > Barra de 3 metros



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Technical Symbols/Marks/Approvals

UL94
V0

GWT
960°

CE

RoHS II

MADE
IN
ITALY

Estándares

EN 61386-1 EN 61386-21

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Sí	Material	Polyvinyl chloride (PVC)	Halogen free	No
Colour	Grey	RAL-number	7035	UV resistant	Sí
Suitable for underground installation	Sí	Operating temperature	-5-60 °C	Bending strength	Rigid
Compressive strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	Impact strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	With sleeve	No
Fire retardant version	Sí	Surface mounting	Sí	Suitable for installation on wood	Sí
Suitable for hollow wall installation	Sí	Suitable for concrete installation	No	Machine and systems installation	Sí
Suitable for underfloor installation (screed)	Sí	Suitable for outdoor installation	Sí	Inner diameter	55.5 mm
Outer diameter	63 mm	High conducting inner coating	No	With metre indication	No

Barcode



8054320284642

Cardboard

15 MT

9 [kg]