

EC220AE16555

VARIABLE EXTERNAL ANGLE DIM. 165X55 mm

Canalizaciones > Pared y techo > Soporte para mecanismos > Serie kuadra - para dispositivos de 45x45mm > Ángulo exterior para canal de pared portamecanismos



IMMAGINE
RAPPRESENTATIVA

REPRESENTATIVE
IMAGE

Technical Symbols/Marks/Approvals

IK08	IP40	GWT 650°	CE	RoHS II	NF	MADE IN ITALY
------	------	-------------	----	---------	----	---------------------

Estándares

EN 50085-1 EN 50085-2-1

Description

Variable external angle for direction changes from 60° to 120°. Snaps onto the channel. Consists of two pieces.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC000872 - Outer corner for wall duct

Degree of protection (IP)	IP40	Material	Plastic	Material quality	Acrylonitrile butadiene styrene (ABS)
Halogen free	Sí	Anti-bacterial treatment	No	Surface protection	Untreated
Colour	White	Impact strength	IK08	Width	165 mm
Depth	55 mm	Model	Moulded hood	RAL-number	9001
Mounting method cover	Spanned	With protective foil	No	Working temperature	-5-60 °C
With cable fixing clip	No	With duct connector	Sí	Bottom perforation	No
Angle	60-120 °	Number of covers	1	Cover width 1	165 mm
Symmetric	Sí				

Documentation available for download



Certification

LICENCE 669929
KUADRA.pdf

Barcode



8033576779027

Unit

1 NR

0.225 [kg]



8032636760838

Cardboard

8 NR

0.39x0.295x0.21 [m]

1.8 [kg]