



IMMAGINE
RAPPRESENTATIVA

EC
REPRESENTATIVE
IMAGE

EC220AI13555

VARIABLE INTERNAL ANGLE DIM. 135X55 mm

Canalizaciones > Pared y techo > Soporte para mecanismos > Serie kuadra - para dispositivos de 45x45mm > Ángulo interior para canal de pared portamecanismos



Technical Symbols/Marks/Approvals

IK08	IP40	GWT 650°	CE	RoHS II	NF	MADE IN ITALY
------	------	-------------	----	---------	----	---------------------

Estándares

EN 50085-1 EN 50085-2-1

Description

Variable internal angle for direction changes from 60° to 120°. Snaps onto the channel. Consists of two pieces.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC000867 - Inner corner for wall duct

Degree of protection (IP)	IP40	Material	Plastic	Material quality	Acrylonitrile butadiene styrene (ABS)
Halogen free	Sí	Anti-bacterial treatment	No	Surface protection	Untreated
Colour	White	Impact strength	IK08	Width	135 mm
Depth	55 mm	Model	Moulded hood	RAL-number	9001
Mounting method cover	Spanned	With protective foil	No	Working temperature	-5-60 °C
With cable fixing clip	No	With duct connector	Sí	Shape	Symmetric
Bottom perforation	No	Angle	60-120 °	Number of covers	1
Cover width 1	135 mm				

Documentation available for download



Certification

LICENCE 669929
KUADRA.pdf

Barcode



8033576778983

Unit

1 NR

0.2 [kg]



8059307212908

Cardboard

10 NR

0.39x0.295x0.21 [m]

2 [kg]