

EC16002H

HORIZ. EXPANSIONS 2+2 DEVICES WITH 60 mm CENTRE HOLE - SLATE GREY



Canalizaciones > Gestión de cables de suelo > Sistemas de distribución de suelo > Cajas de suelo > Caja sobre suelo > Conjuntos de extensión

Technical Symbols/Marks/Approvals

IK07	IP54	GWT 650°	CE	RoHS II	MADE IN ITALY
------	------	-------------	----	---------	---------------------

Estándares

EN 50085-1 EN 50085-2-4

Descripción

Horizontal expansion for double-sided tower made of shock-resistant technopolymer. Designed for 4+4 fixtures with 108.5 mm spacing or for 2+2 fixtures with 60 mm spacing. End cap included for single-sided use. Designed for the entry of 75x17 and 50x12 mm floor trunking. Can be installed on poured or raised floors.

Etim

GROUP EG000005 - Subfloor electrical installation systems

CLASS EC000121 - Surface tank empty


Material	Other	Surface protection	Other	Colour	Anthracite
Width	150 mm	Height	149 mm	Model	Horizontal
Length	176 mm	RAL-number	7021	Number of appliances to build in	8
Number of units to build in front side	4	Number of units to build in rear side	4	Suitable for standard switching equipment	Sí
Suitable for wet cleaning	Sí				

Technical Characteristics

Grado IP	54	Batalla	108 mm
-----------------	----	----------------	--------

Documentation available for download

Instruction booklet



Istruzioni_SERIE_1
60_0423.pdf

Barcode



8033576771793

Unit

1 NR

0.2x0.154x0.145 [m]

0.671 [kg]



8059307212489

Cardboard

10 NR

0.605x0.4x0.35 [m]

6.71 [kg]