



EC893118W10

UNIPOLAR CABLE FS17 1x2,5 mm² BLACK 10 m

Residencial > Utilidades - bricolaje > Cables > Cables > Cable de núcleo único > Cable fs17 - sección 2,5 mm²



Technical Symbols/Marks/Approvals



RoHS II

MADE
IN
ITALY

Estándares

FS17

Etim

GROUP EG000001 - Cables and wires (unassembled)

CLASS EC000993 - Single core single insulated wire

Flame retardant according to IEC 60332-1-2	No	Flame retardant according to IEC 60332-3-21 (Cat A F/R)	No	Flame retardant according to IEC 60332-3-22 (Cat A)	No
Flame retardant according to IEC 60332-3-23 (Cat B)	No	Flame retardant according to IEC 60332-3-24 (Cat C)	No	Flame retardant according to IEC 60332-3-25 (Cat D)	No
Low smoke according to EN IEC 61034-2	No	Halogen free according to EN IEC 60754-1	No	Halogen free according to EN IEC 60754-2	No
Halogen free according to EN IEC 60754-3	No	Reaction-to-fire according to EN 13501-6: Class	Cca	Reaction-to-fire according to EN 13501-6: Smoke production	s3
Reaction-to-fire according to EN 13501-6: Flaming droplets/particles	d1	Reaction-to-fire according to EN 13501-6: Acidity	a3	Outer diameter approximate	4.1 mm
Nominal cross section conductor	2.5 mm ²	Material core insulation	Polyvinyl chloride (PVC)	Core identification	Numbers
Core colour	Black	Conductor material	Copper	Conductor surface	Bare
Conductor category	Class 5 = flexible	Max. permitted conductor temperature	70 °	Oil resistant according to EN IEC 60811-404	No
Nominal voltage U0	750 V	Nominal voltage U	450 V	Processing temperature	5-40 °C
Circuit integrity according to IEC 60331-1	None	Circuit integrity according to IEC 60331-25	None	Low temperature resistant according to EN 60811-504+505+506	No

Barcode



8050507873999

Unit

1 NR

0.302 [kg]



8050507874200

Cardboard

10 NR

3.02 [kg]