

EC34040

DRY LINING INSTALLATION BOX 68X40 - HOLE CENTRE DISTANCE 60



Envolventes > Empotrable > Cajas para mecanismos > 340 -
para paredes de cartón-yeso > Caja, carcasa para montaje
empotrado en pared/techo > Cajas redondas

Technical Symbols/Marks/Approvals

IP40	GWT 850°	CE	RoHS II	MADE IN ITALY
------	-------------	----	---------	---------------------

Estándares

EN 60670-1 EN 60670-22

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002601 - Box/housing for built-in mounting in the wall/ceiling

Mounting method	Hollow wall	Degree of protection (IP)	IP00	Material	Plastic
Halogen free	No	Surface protection	Untreated	Colour	Blue
Width	68 mm	Model	Other	Diameter	71 mm
Cover model	None	Inner depth	40 mm	Circuit integrity	None
Equipped with	None	Shape	Round	Number of inlets	8
Inlet from the rear	Sí	Compliant with BS 4662	No	Couplable	No
Transparent cover	No	Pipe locking	No	Construction type	Built-in installation box (device box)
Airtight	No	For tube diameter	20/25 mm	Cover attachment	Screwed
Sealable	No	With screening	No	Provided with revolving ring	No
Depth	0-40 mm	For number of device inserts	1	Mounting switching equipment	Screwing
With screws	No	Housing feed-through by break-out opening	Sí	Housing feed-through by seal membrane	No
Housing feed-through by nozzle	No	Housing feed-through by step membrane	No	Pipe locking optional	No
Number of included spouts	0	Clamp position fixed	No	Luminaire hook mounting	No
Nozzle	None	Special application	None	With partition panel	No

Barcode



8054320283966

Pack

10 NR

0.068x0.068x0.42 [m]

0.236 [kg]



8057711599509

Cardboard

550 NR

0.41x0.605x0.51 [m]

12.98 [kg]