

## EC400C1A

### SELF-EXTINGUISHING JUNCTION BOX IP44 WITH STEPPED GLANDS DIM. 65X35



Envoltorios > Montaje en pared > Cajas estancas > Serie 400  
- con conos > Caja estanca para montaje en pared > Ip44 -  
autoextinguible v0

#### Technical Symbols/Marks/Approvals

|      |            |             |      |    |         |                     |
|------|------------|-------------|------|----|---------|---------------------|
| IP44 | UL94<br>V0 | GWT<br>960° | IK08 | CE | RoHS II | MADE<br>IN<br>ITALY |
|------|------------|-------------|------|----|---------|---------------------|

#### Estándares

EN 60670-1 EN 60670-22

## Etim

### GROUP EG000048 - Connection material (electrotechnical)

### CLASS EC002600 - Box/housing for surface mounting on the wall/ceiling

|                                    |              |                             |                        |                                     |                          |
|------------------------------------|--------------|-----------------------------|------------------------|-------------------------------------|--------------------------|
| <b>Rated insulation voltage Ui</b> | 400 V        | <b>Mounting method</b>      | Wall-/ceiling mounting | <b>Degree of protection (IP)</b>    | IP44                     |
| <b>Material</b>                    | Plastic      | <b>Halogen free</b>         | No                     | <b>Surface protection</b>           | Untreated                |
| <b>Colour</b>                      | Grey         | <b>Width</b>                | 65 mm                  | <b>Depth</b>                        | 35 mm                    |
| <b>Model</b>                       | Junction box | <b>Diameter</b>             | 65 mm                  | <b>Working temperature</b>          | -25-70 °                 |
| <b>Explosion-tested version</b>    | No           | <b>For Ex-zone gas</b>      | None                   | <b>For Ex-zone dust</b>             | None                     |
| <b>Cover model</b>                 | Blind cover  | <b>Circuit integrity</b>    | None                   | <b>Equipped with</b>                | None                     |
| <b>Shape</b>                       | Round        | <b>Number of inlets</b>     | 4                      | <b>Inlet from the rear</b>          | No                       |
| <b>Transparent cover</b>           | No           | <b>Connectable</b>          | No                     | <b>For tube diameter</b>            | 20 mm                    |
| <b>Mounting in the soil</b>        | No           | <b>Mounting under water</b> | No                     | <b>Type of housing feed-through</b> | Trimmmable step membrane |
| <b>Cover attachment</b>            | Snapped on   | <b>Castable</b>             | No                     | <b>Casting compound included</b>    | No                       |
| <b>Sealable</b>                    | No           | <b>With screening</b>       | No                     | <b>Weatherproof</b>                 | Si                       |

## Barcode



8050880881444

**Pack**

5 NR

0.271 [kg]



8057711590100

**Cardboard**

120 NR

0.39x0.295x0.3 [m]

6.504 [kg]