

EC400C2A

SELF-EXTINGUISHING JUNCTION BOX IP44 WITH STEPPED GLANDS DIM. 80X40



Envoltorios > Montaje en pared > Cajas estancas > Serie 400
- con conos > Caja estanca para montaje en pared > Ip44 -
autoextinguible v0

Technical Symbols/Marks/Approvals

IP44	UL94 V0	GWT 960°	IK08	CE	RoHS II	MADE IN ITALY
------	------------	-------------	------	----	---------	---------------------

Estándares

EN 60670-1 EN 60670-22

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002600 - Box/housing for surface mounting on the wall/ceiling

Rated insulation voltage Ui	400 V	Mounting method	Wall-/ceiling mounting	Degree of protection (IP)	IP44
Material	Plastic	Halogen free	No	Surface protection	Untreated
Colour	Grey	Width	80 mm	Depth	40 mm
Model	Junction box	Diameter	80 mm	Working temperature	-25-70 °
Explosion-tested version	No	For Ex-zone gas	None	For Ex-zone dust	None
Cover model	Blind cover	Circuit integrity	None	Equipped with	None
Shape	Round	Number of inlets	4	Inlet from the rear	No
Transparent cover	No	Connectable	No	For tube diameter	20 mm
Mounting in the soil	No	Mounting under water	No	Type of housing feed-through	Trimable step membrane
Cover attachment	Snapped on	Castable	No	Casting compound included	No
Sealable	No	With screening	No	Weatherproof	Si

Barcode



8050880881451

Pack

5 NR

0.3665 [kg]



8057711590117

Cardboard

150 NR

0.605x0.4x0.35 [m]

10.995 [kg]