

EC400C5

JUNCTION BOX IP55 WITH STEPPED GLANDS DIM. 150X110X70



Envoltorios > Montaje en pared > Cajas estancas > Serie 400
- con conos > Caja estanca para montaje en pared > Ip65

Technical Symbols/Marks/Approvals

IP55	GWT 650°	IK08	CE	RoHS II	MADE IN ITALY
------	-------------	------	----	---------	---------------------

Estándares

EN 60670-1 EN 60670-22

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002600 - Box/housing for surface mounting on the wall/ceiling

Rated insulation voltage Ui	400 V	Mounting method	Wall-/ceiling mounting	Degree of protection (IP)	IP55
Material	Plastic	Halogen free	No	Surface protection	Untreated
Colour	Grey	Width	150 mm	Depth	70 mm
Model	Junction box	Length	110 mm	Diameter	0 mm
Working temperature	-25-70 °	Explosion-tested version	No	For Ex-zone gas	None
For Ex-zone dust	None	Cover model	Blind cover	Circuit integrity	None
Equipped with	None	Shape	Rectangular	Number of inlets	10
Inlet from the rear	No	Transparent cover	No	Connectable	No
For tube diameter	25 mm	Mounting in the soil	No	Mounting under water	No
Type of housing feed-through	Trimmable step membrane	Cover attachment	Screwed	Castable	No
Casting compound included	No	Sealable	No	With screening	No
Weatherproof	Sí				

Documentation available for download



Barcode



8032636761088

Unit

1 NR

0.2644 [kg]



8057711599769

Cardboard

45 NR

0.605x0.4x0.36 [m]

11.898 [kg]