



EC410C10A

SELF-EXTINGUISHING SMOOTH SIDED BOX IP56 DIM. 460X380X120



Envolventes > Montaje en pared > Cajas de conexiones > 410
- paredes lisas > 410 - paredes lisas > Ip56 - autoextinguible v0

Technical Symbols/Marks/Approvals

IP56	UL94 V0	GWT 960°	IK08	CE	RoHS II		MADE IN ITALY
------	------------	-------------	------	----	---------	---	---------------------

Estándares

EN 60670-1 EN 60670-22

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002600 - Box/housing for surface mounting on the wall/ceiling

Rated insulation voltage Ui	400 etim.un.eu570079.abb	Mounting method	Wall-/ceiling mounting	Degree of protection (IP)	IP56
Material	Plastic	Halogen free	No	Surface protection	Untreated
Colour	Grey	Width	460 etim.un.eu570448.abb	Depth	120 etim.un.eu570448.abb
Model	Junction box	Length	380 etim.un.eu570448.abb	Diameter	0 etim.un.eu570448.abb
Working temperature	-25-70 etim.un.eu570073.abb	Explosion-tested version	No	For Ex-zone gas	None
For Ex-zone dust	None	Cover model	Blind cover	Circuit integrity	None
Equipped with	None	Shape	Rectangular	Number of inlets	0
Inlet from the rear	No	Transparent cover	No	Connectable	No
For tube diameter	Other	Mounting in the soil	No	Mounting under water	No
Type of housing feed-through	None	Cover attachment	Screwed	Castable	Yes
Casting compound included	No	Sealable	No	With screening	No
Weatherproof	Yes				

Documentation available for download



Barcode



8032636769985

Unit

1 NR

2.75 [kg]



8059307213615

Cardboard

4 NR

0.605x0.405x0.55 [m]

11 [kg]