

EC410C3

SMOOTH SIDED BOX IP44 DIM. 80X80X40

Envoltorios > Montaje en pared > Cajas estancas > Serie 410 - paredes lisas > Caja estanca para montaje en pared > Ip56 - libre de halógenos



Technical Symbols/Marks/Approvals

IP44	IK08	GWT 650°	HF	CE	RoHS II		MADE IN ITALY
------	------	-------------	----	----	---------	--	---------------------

Estándares

EN 60670-1 EN 60670-22

Descripción

Caja de derivación con paredes lisas y orificios preatornillados. Fabricada en tecnopolímero antichoque a base de ABS resistente a los rayos UV y libre de halógenos. Grado de resistencia al impacto IK08. Resistencia al calor anormal hasta 650°C (GWT). Tapa a presión con cierre a presión, montaje sin herramientas. Posibilidad de doble aislamiento con tapones opcionales. Rosca central posterior M6x6 para fijación a la pared con tacos roscados. Fabricada de conformidad con las normas EN 60670-1:2005 y EN 60670-22:2006. Temperaturas durante la instalación: mínima -5°C, máxima +60°C. Temperaturas de funcionamiento: mínima -25°C, máxima +70°C. Grado de protección IP44. Dimensiones: 80x80x40 mm. 6 entradas preajustadas para tubo de 20 mm de diámetro.

Etim

GROUP EG000048 - Connection material (electrotechnical)


CLASS EC002600 - Box/housing for surface mounting on the wall/ceiling

Rated insulation voltage Ui	400 V	Mounting method	Wall-/ceiling mounting	Degree of protection (IP)	IP44
Material	Plastic	Halogen free	Sí	Surface protection	Untreated
Colour	Grey	Width	80 mm	Depth	40 mm
Model	Junction box	Length	80 mm	Diameter	0 mm
Working temperature	-25-70 °C	Explosion-tested version	No	For Ex-zone gas	None
For Ex-zone dust	None	Cover model	Blind cover	Circuit integrity	None
Equipped with	None	Shape	Square	Number of inlets	6
Inlet from the rear	No	Transparent cover	No	Connectable	No
For tube diameter	20 mm	Mounting in the soil	No	Mounting under water	No
Type of housing feed-through	Preembossing	Cover attachment	Snapped on	Castable	Sí
Casting compound included	No	Sealable	No	With screening	No
Weatherproof	Sí				

Documentation available for download



Dimensions and technical drawings



Barcode



8050880881475

Pack

5 NR

0.3185 [kg]



8057711590131

Cardboard

150 NR

0.605x0.4x0.35 [m]

9.555 [kg]