

EC410C7

SMOOTH SIDED BOX IP56 DIM. 240X140X90



Envolventes > Montaje en pared > Cajas estancas > Serie 410
- paredes lisas > Caja estanca para montaje en pared > Ip56 -
libre de halógenos

Technical Symbols/Marks/Approvals

IP56	GWT 650°	HF	IK08	CE	RoHS II	MADE IN ITALY
------	-------------	----	------	----	---------	---------------------

Estándares

EN 60670-1 EN 60670-22

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002600 - Box/housing for surface mounting on the wall/ceiling

Rated insulation voltage Ui	400 V	Mounting method	Wall-/ceiling mounting	Degree of protection (IP)	IP56
Material	Plastic	Halogen free	Sí	Surface protection	Untreated
Colour	Grey	Width	240 mm	Depth	70 mm
Model	Junction box	Length	190 mm	Diameter	0 mm
Working temperature	-25-70 °C	Explosion-tested version	No	For Ex-zone gas	None
For Ex-zone dust	None	Cover model	Blind cover	Circuit integrity	None
Equipped with	None	Shape	Rectangular	Number of inlets	0
Inlet from the rear	No	Transparent cover	No	Connectable	No
For tube diameter	Other	Mounting in the soil	No	Mounting under water	No
Type of housing feed-through	None	Cover attachment	Screwed	Castable	Sí
Casting compound included	No	Sealable	No	With screening	No
Weatherproof	Sí				

Documentation available for download



Barcode



8032636761446

Unit

1 NR

0.6438 [kg]



8057711599868

Cardboard

16 NR

0.605x0.4x0.36 [m]

10.3008 [kg]