

EC411C3

CABLE JUNCTION BOX 75X75X34 - 12 ENTRIES 8-14 mm



Envolventes > Montaje en pared > Cajas de conexiones > 411
- con pasacables de conexión > Caja, carcasa para montaje en pared/techo

Technical Symbols/Marks/Approvals

IP55	GWT 650°	IK08	HF	CE	RoHS II	MADE IN ITALY
------	-------------	------	----	----	---------	---------------------

Estándares

EN 60670-1 EN 60670-22

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002600 - Box/housing for surface mounting on the wall/ceiling

Max. conductor cross section	14 mm	Rated insulation voltage Ui	400 V	Mounting method	Wall-/ceiling mounting
Degree of protection (IP)	IP55	Material	Plastic	Halogen free	Sí
Surface protection	Untreated	Colour	Grey	Width	75 mm
Depth	34 mm	Model	Junction box	Length	75 mm
Diameter	0 mm	Working temperature	-25-70 °C	Explosion-tested version	No
For Ex-zone gas	None	For Ex-zone dust	None	Cover model	Blind cover
Circuit integrity	None	Equipped with	None	Shape	Square
Number of inlets	12	Inlet from the rear	No	Transparent cover	No
Connectable	No	For tube diameter	16 mm	Mounting in the soil	No
Mounting under water	No	Type of housing feed-through	Seal membrane	Cover attachment	Snapped on
Castable	Sí	Casting compound included	No	Sealable	No
With screening	No	Weatherproof	Sí		

Barcode



8053676577859

Unit

1 NR

0.0604 [kg]



8050880881505

Cardboard

36 NR

0.39x0.295x0.15 [m]

2.1744 [kg]