

EC440C5

SMOOTH SIDED BOX IP56 WITH TRANSPARENT LID DIM. 150X110X140



Envoltorios > Montaje en pared > Cajas de conexiones > 440
- paredes lisas - tapa alta transparente > Cajas de derivación
de pared/serie protegidas y estancas

Technical Symbols/Marks/Approvals

IP56	GWT 650°	HF	IK08	CE	RoHS II	MADE IN ITALY
------	-------------	----	------	----	---------	---------------------

Estándares

EN 60670-1 EN 60670-22

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002600 - Box/housing for surface mounting on the wall/ceiling

Rated insulation voltage Ui	400 etim.un.eu570079.abb	Mounting method	Wall-/ceiling mounting	Degree of protection (IP)	IP56
Material	Plastic	Halogen free	Yes	Surface protection	Untreated
Colour	Grey	Width	150 etim.un.eu570448.abb	Depth	140 etim.un.eu570448.abb
Model	Junction box	Length	140 etim.un.eu570448.abb	Diameter	0 etim.un.eu570448.abb
Working temperature	-25-70 etim.un.eu570073.abb	Explosion-tested version	No	For Ex-zone gas	None
For Ex-zone dust	None	Cover model	Blind cover	Circuit integrity	None
Equipped with	None	Shape	Rectangular	Number of inlets	0
Inlet from the rear	No	Transparent cover	Yes	Connectable	No
Mounting in the soil	No	Mounting under water	No	Type of housing feed-through	None
Cover attachment	Screwed	Castable	Yes	Casting compound included	No
Sealable	No	With screening	No	Weatherproof	Yes

Documentation available for download



Barcode



8032636761613

Unit

1 NR

0.3333 [kg]



8059307213837

Cardboard

18 NR

0.605x0.4x0.35 [m]

5.9994 [kg]