

EC440C9

SMOOTH SIDED BOX IP56 WITH TRANSPARENT LID DIM. 380X300X180



Envoltorios > Montaje en pared > Cajas de conexiones > 440
- paredes lisas - tapa alta transparente > Caja, carcasa para
montaje en pared/techo

Technical Symbols/Marks/Approvals

IP56	GWT 650°	HF	IK08	CE	RoHS II	MADE IN ITALY
------	-------------	----	------	----	---------	---------------------

Estándares

EN 60670-1 EN 60670-22

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002600 - Box/housing for surface mounting on the wall/ceiling

Rated insulation voltage Ui	400 V	Mounting method	Wall-/ceiling mounting	Degree of protection (IP)	IP56
Material	Plastic	Halogen free	Sí	Surface protection	Untreated
Colour	Grey	Width	380 mm	Depth	180 mm
Model	Junction box	Length	300 mm	Diameter	0 mm
Working temperature	-25-70 °C	Explosion-tested version	No	For Ex-zone gas	None
For Ex-zone dust	None	Cover model	Blind cover	Circuit integrity	None
Equipped with	None	Shape	Rectangular	Number of inlets	0
Inlet from the rear	No	Transparent cover	Sí	Connectable	No
Mounting in the soil	No	Mounting under water	No	Type of housing feed-through	None
Cover attachment	Screwed	Castable	Sí	Casting compound included	No
Sealable	No	With screening	No	Weatherproof	Sí

Documentation available for download



Barcode



8032636764676

Unit

1 NR

2.3333 [kg]



8059307213875

Cardboard

3 NR

0.605x0.4x0.36 [m]

6.9999 [kg]