

## EC480C4

### SMOOTH SIDED BOX IP56 POLYCARBONATE DIM. 100X100X50

Envoltorios > Montaje en pared > Cajas de conexiones > 480  
- policarbonato - paredes lisas > 480 - policarbonato - paredes lisas



#### Technical Symbols/Marks/Approvals

|      |       |    |             |      |    |         |   |
|------|-------|----|-------------|------|----|---------|---|
| IP56 | +120° | HF | GWT<br>650° | IK08 | CE | RoHS II | Ⓢ |
|------|-------|----|-------------|------|----|---------|---|

MADE  
IN  
ITALY

#### Estándares

EN 60670-1 EN 60670-22

## Etim

### GROUP EG000048 - Connection material (electrotechnical)

### CLASS EC002600 - Box/housing for surface mounting on the wall/ceiling

|                                     |                                 |                                 |                          |                                  |                         |
|-------------------------------------|---------------------------------|---------------------------------|--------------------------|----------------------------------|-------------------------|
| <b>Rated insulation voltage Ui</b>  | 400<br>etim.un.eu570079.abb     | <b>Mounting method</b>          | Wall-/ceiling mounting   | <b>Degree of protection (IP)</b> | IP56                    |
| <b>Material</b>                     | Plastic                         | <b>Halogen free</b>             | Yes                      | <b>Surface protection</b>        | Untreated               |
| <b>Colour</b>                       | Grey                            | <b>Width</b>                    | 100 etim.un.eu570448.abb | <b>Depth</b>                     | 50 etim.un.eu570448.abb |
| <b>Model</b>                        | Junction box                    | <b>Length</b>                   | 100 etim.un.eu570448.abb | <b>Diameter</b>                  | 0 etim.un.eu570448.abb  |
| <b>Working temperature</b>          | -25-120<br>etim.un.eu570073.abb | <b>Explosion-tested version</b> | No                       | <b>For Ex-zone gas</b>           | None                    |
| <b>For Ex-zone dust</b>             | None                            | <b>Cover model</b>              | Blind cover              | <b>Circuit integrity</b>         | None                    |
| <b>Equipped with</b>                | None                            | <b>Shape</b>                    | Square                   | <b>Number of inlets</b>          | 0                       |
| <b>Inlet from the rear</b>          | No                              | <b>Transparent cover</b>        | No                       | <b>Connectable</b>               | No                      |
| <b>For tube diameter</b>            | Other                           | <b>Mounting in the soil</b>     | No                       | <b>Mounting under water</b>      | No                      |
| <b>Type of housing feed-through</b> | None                            | <b>Cover attachment</b>         | Screwed                  | <b>Castable</b>                  | Yes                     |
| <b>Casting compound included</b>    | No                              | <b>Sealable</b>                 | No                       | <b>With screening</b>            | No                      |
| <b>Weatherproof</b>                 | Yes                             |                                 |                          |                                  |                         |

## Documentation available for download



## Barcode



8032636761804

### Unit

1 NR

0.135 [kg]



8059307214056

### Cardboard

100 NR

0.605x0.4x0.35 [m]

13.5 [kg]