

EC480C4R

SMOOTH SIDED BOX IP56 POLYCARBONATE DIM. 120X80X50

Envolvertes > Montaje en pared > Cajas de conexiones > 480
- policarbonato - paredes lisas > 480 - policarbonato - paredes lisas



Technical Symbols/Marks/Approvals



Estándares

EN 60670-1 EN 60670-22

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002600 - Box/housing for surface mounting on the wall/ceiling

Rated insulation voltage Ui	400 etim.un.eu570079.abb	Mounting method	Wall-/ceiling mounting	Degree of protection (IP)	IP56
Material	Plastic	Halogen free	Yes	Surface protection	Untreated
Colour	Grey	Width	120 etim.un.eu570448.abb	Depth	50 etim.un.eu570448.abb
Model	Junction box	Length	80 etim.un.eu570448.abb	Diameter	0 etim.un.eu570448.abb
Working temperature	-25-120 etim.un.eu570073.abb	Explosion-tested version	No	For Ex-zone gas	None
For Ex-zone dust	None	Cover model	Blind cover	Circuit integrity	None
Equipped with	None	Shape	Rectangular	Number of inlets	0
Inlet from the rear	No	Transparent cover	No	Connectable	No
For tube diameter	Other	Mounting in the soil	No	Mounting under water	No
Type of housing feed-through	None	Cover attachment	Screwed	Castable	Yes
Casting compound included	No	Sealable	No	With screening	No
Weatherproof	Yes				

Documentation available for download



Barcode



8032636761811

Unit

1 NR

0.135 [kg]



8059307214063

Cardboard

100 NR

0.605x0.4x0.35 [m]

13.5 [kg]