

EC491C8A

SELF-EXTINGUISHING JUNCTION BOX IP55 WITH STEPPED GLANDS DIM. 310x230x125 - 1/4 TURN



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Envoltorios > Montaje en pared > Cajas estancas > Serie 49 -
tornillos de plástico de 1/4 de vuelta > Caja estanca para
montaje en pared > Con pasacables - ip55 - autoextinguible v0

Technical Symbols/Marks/Approvals

IP55	UL94 V0	GWT 960°	IK08	CE	RoHS II	MADE IN ITALY
------	------------	-------------	------	----	---------	---------------------

Estándares

EN 60670-1 EN 60670-22

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002600 - Box/housing for surface mounting on the wall/ceiling

Rated insulation voltage Ui	1000 V	Mounting method	Wall-/ceiling mounting	Degree of protection (IP)	IP55
Material	Plastic	Halogen free	No	Surface protection	Untreated
Colour	Grey	Width	310 mm	Depth	125 mm
Model	Junction box	Length	230 mm	Diameter	0 mm
Working temperature	-25-70 °C	Explosion-tested version	No	For Ex-zone gas	None
For Ex-zone dust	None	Cover model	Blind cover	Circuit integrity	None
Equipped with	None	Shape	Rectangular	Number of inlets	12
Inlet from the rear	No	Transparent cover	No	Connectable	No
For tube diameter	32 mm	Mounting in the soil	No	Mounting under water	No
Type of housing feed-through	Trimable step membrane	Cover attachment	Other	Castable	Si
Casting compound included	No	Sealable	Si	With screening	No
Weatherproof	Si				

Documentation available for download



Brochure

Cassette serie
49_IT.pdf

CASSETTE DI DERIVAZIONE
IP67 CON VITI IN ALLUMINIO
PROTEZIONE E PRATICA

elettrocanali

0000

Barcode



8050507875795

Unit

1 NR

1.085 [kg]



8050507876099

Cardboard

6 NR

6.51 [kg]