

EC492C4A

SELF-EXTINGUISHING SMOOTH SIDED BOX IP67 DIM. 110x110x60 - 1/4 TURN



Envolventes > Montaje en pared > Cajas estancas > Serie 49 - tornillos de plástico de 1/4 de vuelta > Caja estanca para montaje en pared > Paredes lisas - ip67 - autoextinguible v0

Technical Symbols/Marks/Approvals

IP67	UL94 V0	GWT 960°	IK08	CE	RoHS II	MADE IN ITALY
------	------------	-------------	------	----	---------	---------------------

Estándares

EN 60670-1 EN 60670-22

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002600 - Box/housing for surface mounting on the wall/ceiling

Rated insulation voltage Ui	1000 V	Mounting method	Wall-/ceiling mounting	Degree of protection (IP)	IP67
Material	Plastic	Halogen free	No	Surface protection	Untreated
Colour	Grey	Width	110 mm	Depth	60 mm
Model	Junction box	Length	110 mm	Diameter	0 mm
Working temperature	-25-70 °C	Explosion-tested version	No	For Ex-zone gas	None
For Ex-zone dust	None	Cover model	Blind cover	Circuit integrity	None
Equipped with	None	Shape	Square	Number of inlets	0
Inlet from the rear	No	Transparent cover	No	Connectable	No
For tube diameter	Other	Mounting in the soil	No	Mounting under water	No
Type of housing feed-through	None	Cover attachment	Other	Castable	Sí
Casting compound included	No	Sealable	Sí	With screening	No
Weatherproof	Sí				

Documentation available for download



Barcode



8050507875825

Unit

1 NR

0.1533 [kg]



8050507876129

Cardboard

90 NR

13.797 [kg]