

EC492C6P



SMOOTH SIDED BOX IP67 POLYCARBONATE DIM. 200x150x85 - 1/4 TURN



IMMAGINE
RAPPRESENTATIVA

EC
REPRESENTATIVE
IMAGE

Envolventes > Montaje en pared > Cajas estancas > Serie 49 -
tornillos de plástico de 1/4 de vuelta > Caja estanca para
montaje en pared > Paredes lisas - ip67 - policarbonato - libre
de halógenos

Technical Symbols/Marks/Approvals

IP67	GWT 650°	HF	+120°	IK08	CE	RoHS II	MADE IN ITALY
------	-------------	----	-------	------	----	---------	---------------------

Estándares

EN 60670-1 EN 60670-22

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002600 - Box/housing for surface mounting on the wall/ceiling

Rated insulation voltage Ui	1000 V	Mounting method	Wall-/ceiling mounting	Degree of protection (IP)	IP67
Material	Plastic	Halogen free	Sí	Surface protection	Untreated
Colour	Grey	Width	200 mm	Depth	85 mm
Model	Junction box	Length	150 mm	Diameter	0 mm
Working temperature	-25-120 °C	Explosion-tested version	No	For Ex-zone gas	None
For Ex-zone dust	None	Cover model	Blind cover	Circuit integrity	None
Equipped with	None	Shape	Rectangular	Number of inlets	0
Inlet from the rear	No	Transparent cover	No	Connectable	No
For tube diameter	Other	Mounting in the soil	No	Mounting under water	No
Type of housing feed-through	None	Cover attachment	Other	Castable	Sí
Casting compound included	No	Sealable	Sí	With screening	No
Weatherproof	Sí				

Documentation available for download



Brochure

Cassette serie
49_IT.pdf

CASSETTE DI DERIVAZIONE
IP20 CON VITI IN ALLUMINIO
PROTEZIONE E PRATICA

elettrocanali

0000

Barcode



8050507875894

Unit

1 NR

0.3705 [kg]



8050507876198

Cardboard

28 NR

0.605x0.4x0.35 [m]

10.374 [kg]