



EC51029

CABLE GLAND THREAD PG 29 GREY WITH LOCK NUT

Envoltorios > Accesorios > Accesorios > Prensaestopas > Prensaestopas > Paso pg - gris - con contratuerca



Technical Symbols/Marks/Approvals

IP68	GWT 650°	CE	RoHS II	MADE IN ITALY
------	----------	----	---------	---------------

Estándares

DIN 40430

Etim

GROUP EG000009 - Cable and wire entry systems

CLASS EC000441 - Cable gland

Degree of protection (IP)	IP68	Material	Plastic	Material quality	Polyamide (PA)
Halogen free	Yes	Surface protection	Untreated	Colour	Grey
Model	Straight	RAL-number	7035	With strain relief	No
Working temperature	-30-90 etim.un.eu570073.abb	Thread type	PG	Nominal thread size metric/PG	29
Pitch thread	1.588 etim.un.eu570448.abb	Glass-fibre reinforced	No	Shock resistant	Yes
Explosion-tested version	No	For Ex-zone gas	None	For Ex-zone dust	None
Pressure-compensating	No	EMC-version	No	Thread length	10.6 etim.un.eu570448.abb
Wrench width	42 etim.un.eu570448.abb	Hexagon angular dimension	60 etim.un.eu570383.abb	Suitable for cable diameter	15-25 etim.un.eu570448.abb
Bend radius protection/trumpet flare	No	With locknut	Yes	Snapping in opening	No
Multi seal area	No	Flat cable coupling	No	Type of sealing	Sealing ring
Separable screw gland	No	For armoured cable	No	Screened	No

Technical Characteristics

Diámetro del orificio de montaje 37
etim.un.eu570448.abb

Barcode



8050880881963

Pack

25 NR

1 [kg]



8057711590414

Cardboard

150 NR

0.39x0.295x0.21 [m]

6 [kg]