

## EC625001



### GRP POLYESTER ENCLOSURE SOLID DOOR 270X305X170 mm

Envolventes > Montaje en pared > Cuadros de poliÉster  
reforzado con fibra de vidrio > Armarios > Armario de  
distribución (vacío) > Puerta ciega




IMMAGINE  
RAPPRESENTATIVA



REPRESENTATIVE  
IMAGE

#### Technical Symbols/Marks/Approvals



#### Estándares

EN 62208

## Etim

### GROUP EG000011 - Enclosures/cabinets

### CLASS EC000261 - Enclosure/cabinet (empty)

|                                                                  |           |                                 |        |                                                                |                                      |
|------------------------------------------------------------------|-----------|---------------------------------|--------|----------------------------------------------------------------|--------------------------------------|
| Degree of protection (IP)                                        | IP66      | Material                        | Other  | Material quality                                               | GRP (Glass fibre reinforced plastic) |
| Surface finishing                                                | Untreated | Colour                          | Grey   | Impact strength                                                | IK10                                 |
| Width                                                            | 270 mm    | Height                          | 305 mm | Depth                                                          | 170 mm                               |
| With cover                                                       | Sí        | RAL-number                      | 7035   | With mounting plate                                            | No                                   |
| Pre-stamping                                                     | No        | EMC-version                     | No     | Suitable for wall mounting                                     | Sí                                   |
| Couplable                                                        | Sí        | Mounting plate depth-adjustable | Sí     | Suitable for wall built-in                                     | No                                   |
| Pole fastening                                                   | Sí        | With door                       | Sí     | Number of doors                                                | 1                                    |
| With glazed door                                                 | No        | With ventilation door           | No     | With rear door                                                 | No                                   |
| Number of locks                                                  | 1         | Transparent cover               | No     | Suitable for outdoor set-up                                    | Sí                                   |
| Pitched roof                                                     | No        | Number of connector holes       | 0      | Thermal dissipation (Delta T = 20 K) according to IEC/TR 60890 | 16 W                                 |
| Max. permitted load of the mounting plate according to IEC 62208 | 10 kg     |                                 |        |                                                                |                                      |

## Documentation available for download



### Instruction booklet

Istruzioni\_625\_042  
3.pdf



### Certification

MI22-0079305-01a  
- ELETTRICANALI  
SPA - HCI\_1 -  
TR\_625.pdf



### Certification

MI22-0079305-01b  
- ELETTRICANALI  
SPA - pH -  
TR\_625.pdf



### Certification

MI22-0079305-01c  
- ELETTRICANALI  
SPA - HCI\_3 -  
TR\_625.pdf



### Certification

MI22-0079343-  
01\_TR\_625.pdf



### Certification

Serie 625  
IMQ\_CA02.06897\_  
2024.pdf



### Brochure

Quadri Poliestere  
IT.pdf



### Brochure

Quadri  
Poliestere\_ENG.pdf

## Barcode



8053676570348

**Unit**

1 NR

0.39x0.295x0.21 [m]

3.15 [kg]