elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET

EC625007

GRP POLYESTER ENCLOSURE SOLID DOOR 190 MODULES (5X38) 800X1055X360 mm

Envolvientes > Montaje en pared > Cuadros de poliÉster reforzado con fibra de vidrio > Armarios > Armario de distribución (vacío) > Puerta ciega

Technical Symbols/Marks/Approvals

IP66 | GWT 960° | UL94 V0 | UV | IK10 | HF | RoHS II | MADE IN ITALY

Estándares

EN 62208

Etim

GROUP EG000011 - Enclosures/cabinets

CLASS EC000261 - Enclosure/cabinet (empty)

Degree of protection (IP)	IP66	**Material**	Other	**Material quality**	GRP (Glass fibre reinforced plastic)
Surface finishing	Untreated	**Colour**	Grey	**Impact strength**	IK10
Width	800 mm	**Height**	1055 mm	**Depth**	360 mm
With cover	Sí	**RAL-number**	7035	**With mounting plate**	No
Pre-stamping	No	**EMC-version**	No	**Suitable for wall mounting**	Sí
Couplable	Sí	**Mounting plate depth-adjustable**	Sí	**Suitable for wall built-in**	No
Pole fastening	No	**With door**	Sí	**Number of doors**	1
With glazed door	No	**With ventilation door**	No	**With rear door**	No
Number of locks	3	**Transparent cover**	No	**Suitable for outdoor set-up**	Sí
Pitched roof	No	**Number of connector holes**	0	**Thermal dissipation (Delta T = 20 K) according to IEC/TR 60890**	160 W
Max. permitted load of the mounting plate according to IEC 62208	100 kg				

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download

Instruction booklet

Istruzioni_625_0423.pdf

Certification

MI22-0079305-01a - ELETTROCANALI SPA - HCl_1 - TR_625.pdf

Certification

MI22-0079305-01b - ELETTROCANALI SPA - pH - TR_625.pdf

Certification

MI22-0079305-01c - ELETTROCANALI SPA - HCl_3 - TR_625.pdf

Certification

MI22-0079343-01_TR_625.pdf

Certification

Serie 625 IMQ_CA02.06897_2024.pdf

Brochure

Quadri Poliestere IT.pdf

Brochure

Quadri Poliestere_ENG.pdf

Barcode

8056351665384

Unit

1 NR

25.85 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.